INSTALLATION AND SAFETY INSTRUCTIONS

IMPORTANT SAFETY INSTRUCTIONS

- Be sure the electricity to the system you are working on is turned off; either the fuse removed or the circuit breaker set at off.
- Use of other manufacturers components will void warranty, listing and create a potential safety hazard.
- To reduce the risk of fire, electric shock, or personal injury, mount to outlet box or supporting system able to support the weight of the fixture.
- If you are unclear as to how to proceed, contact a qualified electrician.
- You don't need special tools to install this fixture.
- Be sure to follow the steps in the order given.
- Under no circumstances should a fixture be hung on house electrical wires, nor should a swag type fixture be installed on a ceiling which contains a radiant type heating system.
- Read instructions carefully.
- Save these instructions.

BEFORE YOU BEGIN

Carefully remove the fixture from the carton and check that all parts are included, as shown in Figures 1 & 2. Be careful not to misplace any of the screws or parts which are needed to install this fixture.



FIGURE 1 *NOT SUPPLIED

GROUNDING AND MOUNTING BAR LOCK UP



FIGURE 2 *NOT SUPPLIED

sea gull lighting®

Installation And Safety Instruction

HC-1150

081507

Fill In Item Number On Carton And
File This Sheet For Fixture Reference. ITEM#_____

INSTALLATION HC-1150

IMPORTANT: DO NOT ATTACH FIXTURE DIRECTLY TO OUTLET BOX.

1. Secure mounting bar (A) to outlet box with outlet box screws (not supplied). Thread nut (B) on nipple (C) so that five threads are exposed above nut (B). Thread this end of nipple (C) into mounting bar (A) and secure by threading nut (B) to mounting bar (A). Thread screw collar (E) onto nipple (C).
2. Using two pairs of pliers, open one link of chain (S) and connect it to the fixture loop (K) at the top of the fixture. Slide the screw collar ring (G) and canopy (H) (in that order) onto the chain (S) and to the top of the fixture.
3. Open one link on the other end of the chain (S) and attach it to screw collar (E).
4. **A**. Take note of the color of the wire(s) on your fixture. Identify which group your fixture wire(s) falls into and connect the wires according to the following directions:
   *Note: When parallel wire is used, the tracer wire is square shaped or ridged and less tracer wire is round in shape or smooth. (Seen best when viewed from wire end.) To separate wires, grasp the ends of each wire and pull apart.



   B. Take your fixture wire(s) from group A and place evenly against the black wire from the outlet box. DO NOT twist wires together before using wire connectors.
   C. Fit a wire connector (not supplied) over the wires and thread the connector clockwise until you feel a firmness.
   D. Try gently to pull the connector off the wires. If you can pull the connector off, carefully re-do steps B and C, as above and check again for a firm connection.
   E. Connect the fixture wire from group B to the white wire from the outlet box in the same manner.
5. **GROUNDING INSTRUCTIONS:** The green grounding screw (D) is to be inserted into the hole with two raised dimples provided on the mounting bar (A). Wrap the ground wire (F) from the fixture (if supplied) and the ground wire from the outlet box (bare metal or green insulated wire) around the green grounding screw (D) on the mounting bar (A). If uninsulated wire is on the mounting bar (A), connect the ground wire (F) from the fixture (if supplied) and the outlet box to it using a small wire connector (not supplied).

NEVER CONNECT GROUND WIRE TO BLACK OR WHITE POWER SUPPLY WIRES.

FINAL ASSEMBLY

Make sure no bare wires can be seen outside wire connectors.

1. After wires are connected, tuck them carefully inside outlet box and then raise the canopy (H), against the ceiling and thread the screw collar ring (G) to the screw collar (E).
2. Install lamps.

CLEANING

To clean, wipe fixture with a soft cloth. Clean glass with a mild soap. Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

ORDERING PARTS

Keep this sheet for future reference, and in case you need to order replacement parts. Parts for this fixture can be ordered from place of purchase. Be sure to use exact wording from illustration when ordering parts.